



TECHNICAL DATA SHEET

Date of issue: 2020

TETRAWOOD HYDRO 250

DESCRIPTION

TETRAWOOD HYDRO from TETRALUX is ecological, water based odorless, acrylic varnish for interior and exterior use.

Certified by ASAOS according to the criteria of Eco labeling Council of EU. It is applied to doors, windows, window frames and any wooden surface, highlighting the natural beauty of the wood and creating a wonderful gloss, satin or matte finish. It has excellent spreading and high resistance to adverse weather conditions without peeling or popping.



TECHNICAL CHARACTERISTICS

Density	: 1,02 - 1,05 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 2.000 - 3.000 mPas (ASTM D2196-86 25°C)
pH	: 8.5 - 9.4 (ASTM E70)
Thinning	: 5 – 10% with water for roller or brush, 10 – 20% for pistol
Coverage	: 9 – 12m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 6 hours
Packaging	: 0.75lt, 2,5lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “e”, Type:WB, Interior/exterior trim varnishes and wood stains, including opaque wood stains: 130g/l (2010). This product contains max 64g/l VOC
Painting tools	: Brush, roller or pistol Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
Conditions of application	: Do not apply at temperatures below 10°C and above 38°C.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2020

Storage : Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances and sanded with suitable sand paper.

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse.

Reuse of paint can effectively minimize the products lifecycle environmental impact. In case of residual paint, keep the container tightly closed after opening and store in dry and cool place out of reach of children. In case of unused residual paint, it is required special handling. Therefore it should not be thrown away into drains, watercourses or soil

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Keep out of reach of children • Empty containers are not used for food storage • Avoid eye and skin contact by using protective equipment and glasses, especially in case of using spraying equipment • In case of skin contact wash immediately with soap and water or suitable skin cleaner • Do not use solvents • In case of eye contact rinse immediately with plenty of water and if it is necessary seek for medical advice • If swallowed, seek immediately for medical advice and show the container or the label • Do not put residual paint down the kitchen sink or toilet or into a waste bin • Disposal of unused paint and empty containers must be performed in compliance with local regulations.

Call POISON CENTER tel. 210 77 93 777 or a doctor if you feel unwell.

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction