



TECHNICAL DATA SHEET

Date of issue: 2020

430 SUPER ECOLUX (EU Ecolabel: EL/044/021)

DESCRIPTION

Excellent quality ecological paint for interior use. It is suitable for walls, concrete, board and plaster. Certified by ASAOS according to the criteria of Eco labeling Council of EU. It provides excellent hiding power and resistance to frequent washing. It spreads evenly, giving a mat surface and has great performance.



TECHNICAL CHARACTERISTICS

Density	: 1,5 - 1,54 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 6000-8000mPas
pH	: 8.5 - 9.4 (ASTM E70)
Resistance to wet abrasion	: 10.000 cycles(DIN 53778)
Thinning	: 5% with water
Coverage	: 12 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Unlimited number of shades through tinting system of TETRALUX.
Packaging	: White: 750ml, 3lt, 10lt Basic shades: 180ml, 375ml, 750ml, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 9g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment and clean it

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2020

immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.

Conditions of application : Do not apply at temperatures below 10°C and above 35°C.

Storage : Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

New surfaces	1° layer: Priming with solvent based or water based primer TETRADUR 2° layer: One layer of Emulsion paint Ecolux 430. Dilution 5% with water 3° layer: One layer of Emulsion paint Ecolux 430. Dilution up to 5% with water
Painted surfaces	Scratch, fill and prime with primer TETRADUR if it's necessary and apply two layers of Emulsion paint Ecolux 430 diluted 5-10% with water

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. In case of residual paint, keep the container tightly closed after opening and store in dry and cool place out of reach of children. In case of unused residual paint, it is required special handling. Therefore it should not be thrown away into drains, watercourses or soil.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Keep out of reach of children • Empty containers are not used for food storage • Avoid eye and skin contact by using protective equipment and glasses, especially in case of using spraying equipment • In case of skin contact wash immediately with soap and water or suitable skin cleaner • Do not use solvents • In case of eye contact rinse immediately with plenty of water and if it is necessary seek for medical advice • If swallowed, seek immediately for medical advice and show the container or the label • Do not put residual paint down the kitchen sink or toilet or into a waste bin • Disposal of unused paint and empty containers must be performed in compliance with local regulations.

Call POISON CENTER tel. 210 77 93 777 or a doctor if you feel unwell.

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2020

methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.