



TECHNICAL DATA SHEET

Date of issue: 2020

ELITE EMULSION PAINT FOR MOULD PROTECTION

DESCRIPTION

Emulsion paint of excellent quality for interior use. It prevents the appearance of mould on the dry film. The ratio of price to quality, makes it unrivalled for putty surfaces. It has great hiding power and high spreading rate.



TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Density | : 1,35 - 1,52 depending on the shade(EAOTENISO 2811 20°C) |
| Viscosity | : 8.000 - 10.000 mPas(ASTM D2196-86 25°C) |
| pH | : 8.6-8.9 (ASTM E70) |
| Resistance to wet abrasion | : >5.000cycles(DIN 53778) |
| Thinning | : 5-10% with water |
| Coverage | : 12m ² /lt per layer |
| Drying time | : Touch dry after 1 hour and recoat able after 2-3hours |
| Colors | : Unlimited number of shades through tinting system of TETRALUX. |
| Packaging | : 750ml, 3lt, 10lt |
| VOC (Volatile Organic Compounds) | : EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25 @60°): 30g/l (2010). This product contains max 29g/l VOC. |
| Painting tools | : Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap. |
| Conditions of application | : Do not apply at temperatures below 10°C and above 35°C. |

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co.L.P.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2020

Storage : Store at temperatures from 5°C to 40°C. Close the container after every use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

| | |
|-------------------------|---|
| New surfaces | 1^olayer: Priming with Acrylic water based primer or water based primer TETRADUR 2^olayer: One layer of Emulsion paint Elite mould protective. Dilution 5-10% with water 3^olayer: One layer of Emulsion paint Elite mould protective. Dilution 5-10% with water |
| Painted surfaces | Sand, fill and prime with Acrylic water based primer or water based TETRADUR if it's necessary and apply two layers of Emulsion paint Elite mould protective diluted 5-10% with water |

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Harmful to aquatic life with long lasting effects • Keep out of reach of children • If medical advice is needed, have product container or label at hand • Avoid release to the environment • Call a POISON CENTER or doctor/physician if you feel unwell • Dispose of contents/container according to the separated collection system used in your municipality.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist
Contains: 1,2-benzisothiazol-3(2H)-one, othilinone (ISO), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction

Tel. POISON CENTER: 210 7793777