

## TECHNICAL DATA SHEET

Date of issue: 2020

### CERA VENEZIANO

#### DESCRIPTION

Special protective gel wax for surfaces decorated with STUCCO VENEZIANO. It waterproofs the surface, emphasizes the shade of the decorative paint and gives a glossy finish.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 0,8 - 0,81 (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: Paste
<b>Thinning</b>	: Without dilution
<b>Coverage</b>	: 8 - 12 m <sup>2</sup> /lit
<b>Packaging</b>	: 750ml, 3lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "i", Type:SB, One-pack performance coatings: 500g/l (2010). This product contains max 499g/l VOC.
<b>Painting tools</b>	: Cotton fabric or long hair glove Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No803.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.



## **TECHNICAL DATA SHEET**

**Date of issue: 2020**

---

### **APPLICATION**

#### **Stir well before use**

Surfaces must be clean, dry and free from foreign objects and substances.

The product does not require dilution.

Apply one thin layer of CERA VENEZIANO with a cotton fabric of a longhair glove and apply it evenly over the entire surface. After 3 hours and after drying, rub gently with a cotton fabric or a lubricant to polish the surface.

---

### **HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION**

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.