

TECHNICAL DATA SHEET

Date of issue: 2020

EFFESTO

DESCRIPTION

Decorative paint that combines 2 materials, with final color that creates reflections and at the same time gives to touch the feeling of rough surface. It is used on any type of wall, furniture, metal frame, etc.



TECHNICAL CHARACTERISTICS

Density	: 0,99 - 1,05 (EΛOT EN ISO 2811 20°C)
Viscosity	: 4.000 - 4.500 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 6 - 8 m ² /lt per layer
Drying time	: Touch dry after 1 hour
Colors	: Many shades through color card of MONDOBELLO
Packaging	: 750ml, 3lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "1", Type:WB, Decorative effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Brush, special glove Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

1st layer: Apply one layer of LEGGENDA with circular and uneven movements using the specific woolen glove.

2nd layer: Apply a layer of EFFESTO crossway, with a synthetic brush.

3rd layer: After completely drying, apply a second layer of EFFESTO in the same way, in order to create a more remarkable result.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.