

TECHNICAL DATA SHEET

Date of issue: 2020

BRILLANTE

DESCRIPTION

Decorative paint for interior and exterior use with metallic reflections that create a climate of high aesthetic and luxury. Suitable for both metal surfaces and walls.



TECHNICAL CHARACTERISTICS

Density	: 1,12 - 1,14 (EΛOT EN ISO 2811 20°C)
Viscosity	: 3.000 - 3.500 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 6 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Many shades through color card of MONDOBELLO
Packaging	: 750ml, 3lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "1", Type:WB, Decorative effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

Metal surfaces	1st layer: One layer of anticorrosive with a color similar to one we chose 2nd layer: After full drying, apply BRILLANTE without dilution with one cross-coat layer for pistol or two layers for brush.
Walls	1st layer: One layer of VELUTTO of same shade with the color we chose 2nd layer: After full drying, apply BRILLANTE without dilution with one cross-coat layer for pistol or two layers for brush.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.