

Elite Kitchen & Bath

Emulsion Paint for protection against fungi and mold

Elite Kitchen & Bath is high quality, mat emulsion paint for interior use in areas with humidity and mold problems. Its special composition prevents the growth of fungi and mold on the dry film and it is suitable for painting walls and ceilings in kitchens, bathrooms and basements.

Characteristics-Advantages

- Odorless
- Easy application without paint splatter
- Perfect spread, excellent performance and great hiding power
- Exceptional whiteness and bright colors
- Velvet , mat finish



TECHNICAL INFORMATION

Product type	Paint based on vinyl-ethylene dispersion of special composition and pigments, aggregates and additives.
Density@25°C	1,45-1,50 gr/ml (for white and bases)
Viscosity @25°C	105,0-110,0 Krebs Units (white and bases)
Drying time @25°C, 50% relative humidity	Touch dry: 40 minutes Recoat: After 2 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)
Colors	White and unlimited number of shades through tinting system of TETRALUX (check the colored products before application in order to avoid differences in shade)
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "a", Type: WB, Interior matt walls and ceilings (Gloss<25@60°): 30g/l (2010). This product contains max 29g/l VOC

DILUTION



5-10% water

APPLICATION



Brush, roller, airless spray gun

DRYING TIME



1 hour

COVERAGE



12m²/l

PACKAGING



0,75l,3l,9l



Technical Data Sheet

Date of issue: 30/5/2022

SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface with TETRACLEAN M from dust, oils, adhesives and loose materials, such as unstable oil coatings, emulsion paints or synthetic plasters. Putty with STUCCOLUX FINE in the places that need filling or layering and then prime, as recommended below:

Type of substrate	Primer
Stable plaster with normal absorbency	-ACRYLIC water based primer dilution 1:3
Porous absorbent plaster	-TETRADUR water based dilution 2:1 -ACRYLIC water based primer dilution 1:1
Putty surface	-TETRADUR water based dilution 2:1
Plaster board	-TETRADUR water based dilution 2:1 or -FILLING plaster board primer for filling and even surface
Concrete	-TETRADUR water based dilution 2:1
Old similar paint	-Direct application -or preventively ACRYLIC water based primer dilution 1:3
Old absorbent paint	-TETRADUR water based dilution 1:1
Hydrochroma	-TETRADUR water based dilution 1:1 first coat -TETRADUR water based dilution 2:1 second coat
Filled cracks, holes, etc	-TETRADUR water based dilution 2:1

*Dilution → Primer: Clean water

DIRECTIONS FOR USE

Application method: Roller, brush, airless spray gun.
Application with Airless gun: Spray angle: 50°/
Nozzle size: 0.018" to 0.021"/ Gun pressure: 150 to 180bar.

Dilution: Dilute with water and stir well

- White 10% v/v
- Base P 10% v/v
- Base D 5-10% v/v
- Base TR to 5% v/v

Application: Apply two coats of **Elite Kitchen & Bath**. Depending on the substrate and the shade, an additional coat may be needed.

Drying time @25°C, 50% Relative humidity:

Touch dry: 40 minutes **Recoat:** After 2 hours. Times may vary depending on the temperature, humidity, film thickness, shade and air movement.

Coverage: 12m²/l per coat on smooth surfaces. On uneven surfaces, consumption will be higher.

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

STORAGE

Keep the containers closed in their initial form and in conditions away from frost, sunlight and temperatures below 5°C or above 35°C.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.