



TECHNICAL DATA SHEET

Date of issue: 2021

911 WATERBASED PRIMER TETRADUR (EU Ecolabel: EL/044/021)

DESCRIPTION

The water based ecological primer TETRADUR is transparent, waterproof acrylic undercoat, with strong adhesion and high penetration. Certified by ASAOS according to the criteria of Eco labeling Council of EU. It is highly recommended for priming surfaces painted with acrylic paints, emulsion paints, RELIEF, cement paint and sealants. It is friendly to environment and to user. It is suitable for the preparation of new surfaces and strengthens and insulates porous surfaces, ensuring better adhesion for the paint.



TECHNICAL CHARACTERISTICS

Density	: 1,00 - 1,02 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 5 mPas (ASTM D2196-86 25°C)
Thinning	: 50 - 100% with water
Coverage	: 15 - 20m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Packaging	: 750ml, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "h", Type:WB, Binding primers: 30g/l (2010). This product contains max 14g/l VOC
Painting tools	: Brush, roller or pistol Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2021

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. In case of residual paint, keep the container tightly closed after opening and store in dry and cool place out of reach of children. In case of unused residual paint, it is required special handling. Therefore it should not be thrown away into drains, watercourses or soil.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.