

TECHNICAL DATA SHEET

Date of issue: 2021

PREMIUM QUALITY ENAMEL PAINT TETRALKYD

DESCRIPTION

High quality enamel paint based on alkyd resins, for interior and exterior use. It is recommended for primed wooden and metallic surfaces. It combines gloss with excellent resistance to adverse weather conditions, maintaining its shades and color. It is easily applied, dries quickly and it has great hiding power. It forms a hard and at the same time flexible film. It is washed up easily.



TECHNICAL CHARACTERISTICS	
Density	: 1,12 – 1,19(EAOTENISO 2811 20°C)
Viscosity	: 105-115 KU (ASTM 562)
Thinning	: 3% with solvent No804
Coverage	: 15 - 16m ² /lt per layer
Drying time	: Touch dry after 2 - 3hours and recoatable after 16 hours
Colors	: Unlimited number of shades through tinting system of TETRALUX
Packaging	: 750ml, 2,5lt, 20lt
VOC (VolatileOrganic	: EU limit value for this product Category A: "d", Type:SB,
Compounds)	Interior/exterior trim and cladding paints for wood and metal: 300g/l (2010). This product contains max 299g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 or No804 and then washwith hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2021

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances. Surfaces must have been sanded.

HEALTH, SAFETYAND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.