



TECHNICAL DATA SHEET

Date of issue: 2020

211 CHALKBOARD PAINT

DESCRIPTION

High quality water-based color, velvet matt, acrylic based, especially designed for painting school boards. It has excellent adhesion, covering and its surface is very resistant to chalking. At the same time it has high resistance to frequent washing or scrubbing. It dries quickly, applies very easily and spreads evenly, offering excellent finish. It is ideal for converting surfaces to chalkboard.



TECHNICAL CHARACTERISTICS

Density	: 1,03 - 1,07 depending on the shade (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 2.500 - 3.500 mPas (ASTM D2196-86 25°C)
Thinning	: 5% with water for brush or roller and 10 – 20% for pistol
Coverage	: 12 - 14 m ² /lt per layer
Drying time	: Touch dry after 30 minutes and recoat able after 5-6 hours
Colors	: Black, tile, cypress and dark shades through tinting system of TETRALUX.
Packaging	: 750ml
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “d”, Type:WB, Interior/external trim and cladding paints for wood and metal: 130g/l (2010). This product contains max 129g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2020

Storage : Store at temperatures from 5°C to 40°C. Close the container after every use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances. It is applied in two layers for a perfect result. It dries in one hour and it can be recoated after 5-6 hours. The time variations may depend on weather conditions. For unpainted or old wooden surfaces, we use as a substrate AQUA PRIMER of TETRALUX. For unpainted or old metal surfaces we use as substrate anticorrosive TETRARUST of TETRALUX.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.