

#### TECHNICAL DATA SHEET

Date of issue: 2020

# **TETRASTONE HYBRID**

#### **DESCRIPTION**

Stone varnish TETRASTONE HYBRID of TETRALUX is a silicone hybrid water based varnish, based on nanotechnology, for porous interior and exterior surfaces. Thanks to its special composition gives excellent penetration, waterproofing and durability to natural materials such as stones of Karystos, Pelion, marble, limestone, as well as in artificial materials such as tiles, bricks, concrete, plaster etc. Prevents yellowing of the surface, mold growth, air pollution and natural wear, offering hardness and strong adhesion.



### TECHNICAL CHARACTERISTICS : 1,00 - 1,10 (ΕΛΟΤ EN ISO 2811 20°C) **Density** Viscosity 250 - 400 mPas (ASTM D2196-86 25°C) : Without dilution **Thinning** 8 - 10m<sup>2</sup>/lt per layer Coverage **Drying time** : Touch dry after 30 minutes and recoat able after 1 - 2 hours : 0.75lt, 2,5lt, 10lt **Packaging VOC** (Volatile Organic EU limit value for this product Category A: "i", Type:WB, One-pack performance coatings: 140g/l (2010). This product contains max 139g/l **Compounds**) VOC : Brush, roller or pistol **Painting tools** Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap. : Do not apply at temperatures below 10°C and above 35°C. **Conditions of application** Store at temperatures from 5°C to 40°C. Close the container after every **Storage** use.



#### **TECHNICAL DATA SHEET**

Date of issue: 2020

# **APPLICATION**

### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances. Apply the product to the most possible amount.

# HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.