



## TECHNICAL DATA SHEET

Date of issue: 2020

# 470 GRASSLINE

## DESCRIPTION

Concentrated marking paint with high coverage and whiteness for grass. It is distinguished for fast drying, adhesion and great resistance to water. It is biodegradable and does not contain solvents and plasticizers that cause problems in the grass.



## TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,36 - 1,37 depending on the shade (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 1.300 - 1.500 mPas (ASTM D2196-86 25°C)
<b>Thinning</b>	: 0 - 100% with water
<b>Coverage</b>	: 10 lt per football field
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 2-3hours
<b>Colors</b>	: White
<b>Packaging</b>	: 3lt, 10lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "i", Type:WB, One-pack performance coatings: 140g/l (2010). This product contains max 139g/l VOC.
<b>Painting tools</b>	: Road marking machine Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



## **TECHNICAL DATA SHEET**

**Date of issue: 2020**

---

### **APPLICATION**

#### **Stir well before use**

For the application use a road marking machine.

### **HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION**

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.