



## TECHNICAL DATA SHEET

Date of issue: 2021

### ACRYLIC PAINT PANCHROM

#### DESCRIPTION

Professional acrylic paint with good resistance to adverse weather conditions and high hiding power and covering.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,57±0.02 (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 110 - 120 KU (ASTM 562)
<b>Thinning</b>	: 5 - 10% with water
<b>Coverage</b>	: 10 - 12 m <sup>2</sup> /l per layer
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 2-3hours
<b>Colors</b>	: Unlimited number of shades through tinting system of TETRALUX.
<b>Packaging</b>	: 750ml, 3lt, 9lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "c", Type:WB, Exterior walls of mineral substrate: 40g/l (2010). This product contains max 39g/l VOC.
<b>Painting tools</b>	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)



## TECHNICAL DATA SHEET

Date of issue: 2021

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

<b>New surfaces</b>	<b>1<sup>o</sup> layer:</b> Priming with solvent based or water based primer TETRADUR <b>2<sup>o</sup> layer:</b> One layer of Acrylic Panchrom. Dilution 5-10% with water <b>3<sup>o</sup> layer:</b> One layer of Acrylic Panchrom. Dilution up to 5-10% with water
<b>Painted surfaces</b>	Scraping, puttying and priming with primer TETRADUR if it's necessary and application of two layers of Acrylic Panchrom diluted 5-10% with water

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.