

#### TECHNICAL DATA SHEET

Date of issue: 2021

# SILVERLUX

#### **DESCRIPTION**

Excellent quality water based aluminum-colored paint for terraces. It has strong reflective properties, reducing the substrate temperature, making it suitable for protecting terraces from solar radiation. For better results apply to surfaces covered with asphaltic waterproofing membranes offering a smooth, shiny finish. The film created is elastic, as it follows the contractions / expansions of the membrane, avoiding cracking.



### TECHNICAL CHARACTERISTICS **Density** : 1,00 - 1,03 (EAOT EN ISO 2811 20°C) : 80 - 85 KU (ASTM 562) Viscosity : Without dilution **Thinning** : 10 m<sup>2</sup>/lt per layer Coverage Touch dry after 30 minutes and recoat able after 2hours **Drying time** : Silver **Colors** : 3lt, 16lt **Packaging** VOC (Volatile Organic : EU limit value for this product Category A: "c", Type:WB, Exterior walls of mineral substrate: 40g/l (2010). This product contains max **Compounds**) 39g/1 VOC. **Painting tools** : Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap. **Conditions of application** : Do not apply at temperatures below 10°C and above 35°C. Storage Store at temperatures from 5°C to 40°C. Close the container after every



#### **TECHNICAL DATA SHEET**

Date of issue: 2021

# **APPLICATION**

### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances
The product is ready to use and is used without dilution. Stir well during use. It must be used at least 15 days after asphaltic membrane application.

## HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.