



## TECHNICAL DATA SHEET

Date of issue: 2020

# STUCCOLIGHT

## DESCRIPTION

Stuccolight of TETRALUX is lightweight, elastic, acrylic putty, in paste form, ready to use. It is suitable for filling holes and cracks quickly, regardless of their size, for interior and exterior surfaces (walls, ceilings, mortar, concrete, plaster board, wood etc). It is easily applicable, quick drying and non crackling. It has a great filling capability with a single use and zero shrinkage. No sanding is required.



## TECHNICAL CHARACTERISTICS

<b>Density</b>	: 0,36 (EAOT EN ISO 2811 20°C)
<b>Thinning</b>	: Without dilution
<b>Coverage</b>	: It depends on application
<b>Drying time</b>	: Touch dry after 30 min and it's painted after 1-2hours depending on substrate's absorbance
<b>Packaging</b>	: 750ml
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "g", Type:WB, Primers: 30g/l (2010). This product contains max 29g/l VOC.
<b>Painting tools</b>	: Spatula Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.



## TECHNICAL DATA SHEET

Date of issue: 2020

### APPLICATION

#### Stir well before use

Cracks and surfaces must be clean, dry and free from foreign objects and substances.

<b>New and previously painted surfaces</b>	It is applied without dilution on cracks and before the product is dried, the surface must be smoothed with a wet brush or spatula. After 1-2 hours it can be painted with emulsion or acrylic, water or solvent based paints.
--	--

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.