



## TECHNICAL DATA SHEET

Date of issue: 2021

### ACRYLIC WATERBASED PRIMER

#### DESCRIPTION

It is a whitish water based undercoat for emulsion and acrylic paints. Creates better adhesion conditions and stabilizes the surface. It has very high coverage and is the most economic wall primer.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,29 - 1,32 (ΕΛΟΤ EN ISO 2811 20°C)
<b>Viscosity</b>	: 5.000 - 7.000 mPas (ASTM D2196-86 25°C)
<b>Thinning</b>	: Dilute with water at a ratio of 1 part primer 4 parts water
<b>Coverage</b>	: 25 - 30m <sup>2</sup> /lt per layer
<b>Drying time</b>	: Touch dry after 1 hour
<b>Packaging</b>	: 0.75lt, 3lt, 10lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "g", Type:WB, primers: 30g/l (2010). This product contains max 29g/l VOC
<b>Painting tools</b>	: Brush, roller or pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)



## **TECHNICAL DATA SHEET**

**Date of issue: 2021**

---

### **APPLICATION**

#### **Stir well before use**

---

Surfaces must be clean, dry and free from foreign objects and substances

---

### **HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION**

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.