



TECHNICAL DATA SHEET

Date of issue: 2021

PLASTER BOARD PRIMER

DESCRIPTION

The plaster board primer is a white acrylic undercoat for interior use with strong adhesion and high filling capacity. Ideal for plaster board, concrete, plaster, etc. because it assimilates the absorbency of the surface with the jointing materials and at the same time covers dissimilarities. It can be tinted (light shades) by Tetralux tinting system for a better final result.



TECHNICAL CHARACTERISTICS

| | |
|---|---|
| Density | : 1,72 - 1,74 (EAOT EN ISO 2811 20°C) |
| Viscosity | : 10.000 - 13.500 mPas (ASTM D2196-86 25°C) |
| Thinning | : 5 – 10% with water |
| Coverage | : 10 - 12m ² /lt per layer |
| Drying time | : Touch dry after 1 hour and recoat able after 2-3hours |
| Packaging | : 750ml, 3lt, 9lt |
| VOC (Volatile Organic Compounds) | : EU limit value for this product Category A: “h”, Type:WB, Binding primers: 30g/l (2010). This product contains max 29g/l VOC |
| Painting tools | : Brush, roller or pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap. |
| Conditions of application | : Do not apply at temperatures below 10°C and above 35°C. |
| Storage | : Store at temperatures from 5°C to 40°C. Close the container after every use. |

APPLICATION

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2021

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.