



## TECHNICAL DATA SHEET

Date of issue: 2021

### SOLVENT BASED PRIMER TETRADUR 910

#### DESCRIPTION

The solvent based primer TETRADUR is transparent, micronized, waterproof, acrylic undercoat, with strong adhesion and high penetration. It is highly recommended for priming surfaces painted with acrylic paints, emulsion paints, RELIEF, cement paint and sealants. It is suitable for the preparation of new surfaces and further strengthens and insulates porous surfaces, ensuring better adhesion for the paint. Waterproofs the surface while let it breathe.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 0,82 - 0,92 (ΕΛΟΤ EN ISO 2811 20°C)
<b>Viscosity</b>	: 20 - 35 mPas (ASTM D2196-86 25°C)
<b>Thinning</b>	: 20 - 100% with solvent No804
<b>Coverage</b>	: 13 - 15 m <sup>2</sup> /l per layer depends on the dilution and the surface absorption
<b>Drying time</b>	: Touch dry after 1 hour and top coat application after 2 – 3 hours (Time may depend on temperature, humidity, film thickness and air movement).
<b>Colors</b>	: Transparent
<b>Packaging</b>	: 750ml, 5l, 20l
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: “h”, Type:SB, Binding primers: 750g/l (2010). This product contains max 749g/l VOC.
<b>Painting tools</b>	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 or No804 and then wash with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)



## TECHNICAL DATA SHEET

Date of issue: 2021

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

<b>Dilution</b>	Walls: Up to 100% with solvent No 804 of <b>TETRALUX</b> . Terraces: Up to 20% with solvent No 804 of <b>TETRALUX</b> .
<b>Coverage</b>	Walls: Covers 13-15m <sup>2</sup> /lt per layer, depend on dilution and surface absorption Terraces: Covers 8-10m <sup>2</sup> /lt per layer, depend on dilution and surface absorption

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.