

## TECHNICAL DATA SHEET

Date of issue: 2020

### CELLESTE

#### DESCRIPTION

Decorative paint in light, preferably shades, with shades and clouds.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,05 - 1,07 (EΛOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 8.000 - 9.500 mPas (ASTM D2196-86 25°C)
<b>Thinning</b>	: Without dilution
<b>Coverage</b>	: 12 - 16 m <sup>2</sup> /lt per layer
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 2-3hours
<b>Colors</b>	: Many shades through color card of MONDOBELLO
<b>Packaging</b>	: 750ml, 3lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "1", Type:WB, Decorative effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
<b>Painting tools</b>	: Brush, plastic spatula  Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.



## TECHNICAL DATA SHEET

Date of issue: 2020

---

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

**1<sup>st</sup> layer :** One layer of VELUTTO in a very lighter or darker shade than the one we chose

**2<sup>nd</sup> layer:** After full drying we apply CELLESTE using a brush or patron with crosswise movements and a roll for large surfaces. Before drying, create the final effect, with the special spatula, with irregularly cut spatula, preferably until the desired effect.

---

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.