

TECHNICAL DATA SHEET

Date of issue: 2020

CHALK VARNISH

DESCRIPTION

Mondo bello's CHALK VARNISH is a water-based, acrylic based varnish for chalk paint. Ideal for the protection and sealing of surfaces painted with CHALK PAINT of TETRALUX. It strengthens and highlights the tone of the chalk paint while it is easy to apply, it's non yellowing and dries quickly. Protects against moisture, daily damage and it can be washed with soap and water. It has excellent spreading and great durability without peeling or popping creating a wonderful gloss, satin or matte finish.



TECHNICAL CHARACTERISTICS	
Density	: 1,03 - 1,05 (EAOT EN ISO 2811 20°C)
Viscosity	: 2.500 - 3.500 mPas (ASTM D2196-86 25°C)
Thinning	: Up to 30% with water for roller, brush or pistol
Coverage	: 9 – 12m²/lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 6 hours
Packaging	: 375ml, 750ml
VOC (Volatile Organic	: EU limit value for this product Category A: "e", Type: WB,
Compounds)	Interior/exterior trim varnishes and wood stains, including opaque wood stains: 130g/l (2010). This product contains max 129g/l VOC
Painting tools	: Brush, roller or pistol
	Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.



TECHNICAL DATA SHEET

Date of issue: 2020

Storage : Store at temperatures from 5°C to 40°C. Close the container after every use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances and sanded with suitable sand paper.

Apply thin layers with a good quality brush or roller. The surface must be wiped out in order to avoid paintbrush lines.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.