

TECHNICAL DATA SHEET

Date of issue:2020

CHALK WAX

DESCRIPTION

Chalk wax of Mondo bello is a special finishing wax paste applied to surfaces painted with Chalk paint of Mondo bello. Suitable for extra protection of chalk paint, offering a velvet and smooth surface. Protects the surface from scratches and moisture, while enhancing the tone of chalk paint or natural wood. It is a low odor product.



TECHNICAL CHARACTERISTICS

| | |
|---|--|
| Density | : 0,80 – 0,82(EΛΟΤΕΝΙΣΟ 2811 20°C) |
| Thinning | : Without dilution |
| Coverage | : 15m ² /lt |
| Drying time | : Touch dry after 30 minutes |
| Colors | : Transparent, antique, white, black, amber |
| Packaging | : 250ml |
| VOC (Volatile Organic Compounds) | : EU limit value for this product Category A: “i”, Type:SB, One-pack performance coatings: 500g/l (2010). This product contains max 499g/l VOC. |
| Painting tools | : Brush, cotton fabric Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 or No803 and then wash with hot water and soap. |
| Conditions of application | : Do not apply at temperatures below 10°C and above 35°C. |
| Storage | : Store at temperatures from 5°C to 40°C. Close the container after every use. |



TECHNICAL DATA SHEET

Date of issue:2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

It is applied with a good quality brush or a cotton fabric after the painting of the surfaces with Chalk paint.

Apply a thin layer and after it is dried, apply the second. Between the layers wait for 30 minutes so the wax is absorbed by the surface.

Dries after 1-2 hours. Coverage : 15m²/lt

Product for artistic use.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.