



## TECHNICAL DATA SHEET

Date of issue: 2021

### EMULSION PAINT ELITE BASIC

#### DESCRIPTION

Emulsion paint of excellent quality for interior use. It has great hiding power and high spreading rate. Also available in basic shades for coloring emulsion and acrylic paints.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,29 - 1,50 depending on the shade (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 6500 - 9500cP (ASTM D2196-86 25°C)
<b>Coverage</b>	: 12 m <sup>2</sup> /lt per layer
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 2-3hours
<b>Colors</b>	: Black,blue,red,yellow,ocher,tile,green,brown,orange
<b>Packaging</b>	: 180ml, 375ml, 750ml, 3lt, 10lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 29g/l VOC.
<b>Painting tools</b>	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



## TECHNICAL DATA SHEET

Date of issue: 2021

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

<b>New surfaces</b>	<b>1<sup>o</sup> layer:</b> Priming with Acrylic water based primer or water based primer TETRADUR <b>2<sup>o</sup> layer:</b> One layer of Emulsion paint Elite. Dilution 5-10% with water <b>3<sup>o</sup> layer:</b> One layer of Emulsion paint Elite. Dilution up to 5-10% with water
<b>Painted surfaces</b>	Scraping, puttying and priming with Acrylic water based primer or primer TETRADUR if it's necessary and application of two layers of Emulsion paint Elite diluted 5-10% with water

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)