



## TECHNICAL DATA SHEET

Date of issue: 2021

### VELVET EMULSION PAINT (EU Ecolabel: EL/044/021)

#### DESCRIPTION

Ecological paint for interior use. It is suitable for walls, concrete, board and plaster. Certified by ASAOS according to the criteria of Eco labeling Council of EU. It's economical, providing great hiding power and spreading rate. It is suitable for professional use.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,52 - 1,63 depending on the shade (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 105 - 115 KU (ASTM D2196-86 25°C)
<b>Resistance to wet abrasion</b>	: >1.000 cycles(DIN 53778)
<b>Thinning</b>	: 5 - 10% with water
<b>Coverage</b>	: 10-13 m <sup>2</sup> /l per layer
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 2-3hours
<b>Colors</b>	: Unlimited number of shades through tinting system of TETRALUX.
<b>Packaging</b>	: White-Bases: 750ml, 3lt, 9lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 9g/l VOC.
<b>Painting tools</b>	: Brush, roller, pistol  Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)



## TECHNICAL DATA SHEET

Date of issue: 2021

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

<b>New surfaces</b>	<b>1<sup>o</sup> layer:</b> Priming with Acrylic water based primer or water based primer TETRADUR <b>2<sup>o</sup> layer:</b> One layer of Emulsion paint Velvet. Dilution 5-10% with water <b>3<sup>o</sup> layer:</b> One layer of Emulsion paint Velvet. Dilution up to 5-10% with water
<b>Painted surfaces</b>	Scraping, puttying and priming with Acrylic water based primer or water based primer TETRADUR if it's necessary and application of two layers of Emulsion paint Velvet diluted 5-10% with water.

Minimize paint wastage by estimating how much paint you will need. Recover unused paint for reuse. Reuse of paint can effectively minimize the products life cycle environmental impact. In case of residual paint, keep the container tightly closed after opening and store in dry and cool place out of reach of children. In case of unused residual paint, it is required special handling. Therefore it should not be thrown away into drains, watercourses or soil.

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.