

TECHNICAL DATA SHEET Date of issue: 2020

LEGGENDA

DESCRIPTION

Decorative paint mainly applied on a light background, preferably white or beige. The rough surface and the final visual effect give a picture of old house walls.



TECHNICAL CHARACTERISTICS	
Density	: 1,13 - 1,15 (EAOT EN ISO 2811 20°C)
Viscosity	: 7.000 - 9.000 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: $4 - 6 \text{ m}^2/\text{lt per layer}$
Drying time	: Touch dry after 1 hour and recoatable after $2 - 3$ hours
Colors	: Many shades through color card of MONDOBELLO
Packaging	: 750ml, 3lt
VOC (Volatile Organic	: EU limit value for this product Category A: "l", Type:WB, Decorative
Compounds)	effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Brush, special glove, plastic spatula
	Remove as much paint as possible from the equipment in the container
	and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every
	use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E. 5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET Date of issue: 2020

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

 1^{st} layer: On a white or bright surface apply LEGGENDA by using a brush or the specific woolen glove 2^{nd} layer: After completely drying, apply the second layer of LEGGENDA. Before drying create the final

effect with soft movements using the specific slice-spatula, covering the entire surface

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.