

TECHNICAL DATA SHEET

Date of issue: 2020

PELLE

DESCRIPTION

Transparent matt decorative paint that gives the impression of a leathery, extremely smooth surface and at the same time enhances the durability of the painted surface.



TECHNICAL CHARACTERISTICS

Density	: 1,00 - 1,02 (EΛOT EN ISO 2811 20°C)
Viscosity	: 200 - 250 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 12 - 15 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoatable after 2 – 3 hours
Colors	: Trasparent
Packaging	: 750ml, 3lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “1”, Type:WB, Decorative effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Roller Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

1st layer: Apply one layer of the desired shade of VELLUTTO or a high-quality plastic paint so that our surface is smooth and non-absorbent.

2nd layer: Apply PELLE over the entire surface with a roll (short tread - hair)

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.