

TECHNICAL DATA SHEET

Date of issue: 2020

PERLA

DESCRIPTION

Decorative paint with impressive final satin effect that adds luxury to the interior walls of houses, hotels, etc.



TECHNICAL CHARACTERISTICS

Density	: 1,07 - 1,12 (EΛOT EN ISO 2811 20°C)
Viscosity	: 10.000 – 13.500 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 6 - 7 m ² /lt per layer
Drying time	: Touch dry after 1 hour
Colors	: Many shades through color card of MONDOBELLO
Packaging	: 750ml, 3lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "1", Type:WB, Decorative effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Roller, special glove Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

APPLICATION



TECHNICAL DATA SHEET

Date of issue: 2020

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

1st layer: Apply a layer of VELLUTO in white or bright tint.

2nd layer: Apply a layer of PERLA with the special woolen glove or a roller for large surfaces

3rd layer: After completely drying, apply the second layer of PERLA with circular and uneven movements, leaving generous amount of paint on the surface.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.