

TECHNICAL DATA SHEET

Date of issue: 2020

SABBIOSO

DESCRIPTION

Decorative paint in gold or silver with sandy texture and metallic flashes. It is colored and applied on a light or dark background.



TECHNICAL CHARACTERISTICS	
Density	: 0,90 - 1,00 (EAOT EN ISO 2811 20°C)
Viscosity	: 17.000 – 20.000 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 10 - 12 m ² /lt per layer
Drying time	: Touch dry after 1 hour
Colors	: Many shades through color card of MONDOBELLO
Packaging	: 750ml, 3lt
VOC (Volatile Organic	: EU limit value for this product Category A: "1", Type:WB, Decorative
Compounds)	effect coatings: 200g/l (2010). This product contains max 40g/l VOC.
Painting tools	: Brush
	Remove as much paint as possible from the equipment in the container
	and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every
	use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

1st layer: Apply a layer of VELLUTO in any desired shade.

2nd layer: a .Apply a layer of SABBIOSO with a synthetic brush, making crossing moves, leaving unevenly the material on the surface.

- **b.** "Comb" the surface with the brush without material, vertical-horizontal and oblique until the desired result.
- c. For extra protection apply a water based glossy varnish MONDO BELLO.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.