



TECHNICAL DATA SHEET

Date of issue: 2021

SOLVENTBASED WOOD PROTECTIVE TETRAXYL

DESCRIPTION

Protective and decorative high quality product for all wood surfaces.

It prevents the appearance of mold and fungi on the surface of the dry film. It protects wood against the damaging effects of UV light,

it's resistant to UV rays and provides maximum protection. It

maintains its elasticity following the expansion or contraction of the

wood without breaking it. It is used for interior and exterior wooden

surfaces such as doors, windows, shutters, fences, shelters, pergolas,

roofs etc. It is available in various shades from Woodstains color

card of TETRALUX.



TECHNICAL CHARACTERISTICS

Density	: 0,83 – 0,86 (EAOTENISO 2811 20°C)
Viscosity	: 10 – 20mPas(ASTMD2196-86 25°C)
Coverage	: 12m ² /lt per layer
Drying time	: Touch dry after 1 – 2 hours and recoat able after 3 – 4hours
Colors	: It is available in various shades from Woodstains color card of TETRALUX.
Packaging	: 750ml, 2.5lt, 5lt, 20lt
VOC (VolatileOrganic Compounds)	: EU limit value for this product Category A: “h”, Type:SB, Binding primers: 750g/l (2010). This product contains max 749g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No804 or 806 and then washwith hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS&CoE.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2021

APPLICATION

Stir well before use

Surfaces must be clean, dry, free of foreign matter and substances such as oils, dusts, etc. Remove defective previous coatings. It is applied in two or three layers depending on the type of wood and its absorbency. (Effective fungi protection at 180ml / m²). Low temperature, increased humidity and certain types of wood can increase drying time.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.