



TECHNICAL DATA SHEET

Date of issue: 2020

TETRAWOOD HYDRO

DESCRIPTION

TETRAWOOD HYDRO is water based odorless, acrylic varnish for interior and exterior use. It is applied to doors, windows, window frames and any wooden surface, highlighting the natural beauty of the wood and creating a wonderful gloss, satin or matte finish. It has excellent spreading and high resistance to adverse weather conditions without peeling or cracking.



TECHNICAL CHARACTERISTICS

Density	: 1,02 - 1,05 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 2.000 - 3.000 mPas (ASTM D2196-86 25°C)
Thinning	: 5 - 10% with water for roller or brush, 10 – 20% for pistol
Coverage	: 9 - 12m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 6 hours
Packaging	: 0.75lt, 2,5lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “e”, Type:WB, Interior/exterior trim varnishes and wood stains, including opaque wood stains: 130g/l (2010). This product contains max 64g/l VOC
Painting tools	: Brush, roller or pistol Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances and sanded with suitable sand paper.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.