



TECHNICAL DATA SHEET

Date of issue: 2022

THERMOLUX INTERIOR

DESCRIPTION

THERMOLUX interior is an excellent quality thermo insulating paint for interior walls. It prevents the appearance of mold on the dry film and it contributes to energy saving. It is suitable for every kind of new or old surface such as plaster, concrete etc. and the result is a magnificent mat surface with great resistance to frequent washing.



TECHNICAL CHARACTERISTICS

Density	: 1,08 - 1,15(EAOT EN ISO 2811 20°C)
Viscosity	: 93-101KU (ASTM D562)
Resistance to wet abrasion	: 10.000 cycles(DIN 53778)
Thinning	: 5 % with water
Coverage	: 12 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Unlimited number of shades through tinting system of TETRALUX.
Packaging	: 750ml, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25 @ 60th): 30g/l (2010). This product contains max 29g/l VOC
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2022

Storage : Store at temperatures from 5°C to 40°C. Close the container after every use.

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

If the surface is affected by mold, requires cleaning with antimould liquid or bleach solution in water. This process is recommended at least twice. For maximum energy efficiency film thickness of 300µm is required and usually achieved by the third layer.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.