



## TECHNICAL DATA SHEET

Date of issue: 2023

# SOLLIEVO

## DESCRIPTION

Acrylic, decorative coating ready to use. It has excellent adhesion to all masonry types like concrete, plaster, cement, etc. Does not need to be over-coated by paint. Due to its elasticity, it is ideal as topcoat to the constructions for subsequent insulation of buildings.

## TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,74 - 1,83 (ΕΛΟΤ EN ISO 2811 20°C)
<b>Viscosity</b>	: 45.000 - 55.000 mPas (ASTM D2196-86 25°C)
<b>Thermal conductivity</b>	: $\lambda=0,7$ W(mk)
<b>Thinning</b>	: Without dilution
<b>Coverage</b>	: 0,4mm: 1,3 έως 1,5 kg/m <sup>2</sup>
<b>Drying time</b>	: Touch dry after 1 hour at 25°C
<b>Colors</b>	: Unlimited number of shades through tinting system of TETRALUX. -The raw materials (natural stones and artificial glass beads) in the Sollievo, may produce small differences in the tinting, so it is recommended the tinting of same batches)
<b>Packaging</b>	: 25kg
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: "i", Type:WB, One pack performance coatings: 140g/l (2010). This product contains <140g/l VOC.
<b>Painting tools</b>	: Spatula or appropriate machine  Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 8°C and above 38°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)



## TECHNICAL DATA SHEET

Date of issue: 2023

---

### APPLICATION

#### Stir well before use

The substrate must be clean, dry and free of foreign matter and substances. First apply a layer with the special PRIMER SOLLIEVO. After the primer dries, stir the material well and apply using a stainless polished spatula or an appropriate machine. While the SOLLIEVO layer is fresh (about 5-15 minutes later), the surface is 'pressed' or 'scrubbed' using a plastic spatula. Do not apply at temperatures below 8°C and above 38°C and in conditions of relative humidity above 80%.

---

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Keep out of reach of children • If medical advice is needed, have product container or label at hand • Do not get in eyes, on skin, or on clothing. • Call a POISON CENTER or doctor/physician if you feel unwell •

Dispose of contents/container in accordance with applicable regional, national and local laws and regulations

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist

Contains: Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

Tel. POISON CENTER: 210 7793777