

TILELUX

Paint for wall tiles

TILELUX is a high quality satin water-based enamel paint specially designed for wall tiles. Its composition and the use of the special STEPlus additive makes it unique for painting tile surfaces exposed to a particularly harsh and humid environment. It is characterized by excellent adhesion even on glossy tiles (>6Mpa) and by its excellent resistance to wet environments, to the use of shampoos, shower gels, classic cleaning products, anti-salt products, diluted bleach, white vinegar and hot-cold water alternation. It is a unique solution for bathroom and shower renovation.

Characteristics-Properties


- Easy application
- Excellent finish
- No primer needed
- Excellent adhesion
- Excellent resistance to wet environment
- Excellent resistance to cleaners, bath products, hot-cold water alternation




TECHNICAL INFORMATION

Product Type	Special waterborne enamel paint based on aqueous polymer dispersions of suitable composition and selected pigments, aggregates and additives
Density @25°C	1,22±0,01 gr/ml
Viscosity @25°C	95-100 Krebs Units
Drying Times @25°C, 50% Relative Humidity	Within 60 minutes Recoat: after 6 hours These times may vary depending on temperature, humidity, film thickness and air mobility.
Shades	In white and 5 other shades
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "j", Type: WB, Two-pack reactive performance coatings for specific end use such as floors: 140g/l (2010). This product contains max 10g/l VOC

DILUTION



APPLICATION



DRYING TIME



COVERAGE



PACKAGING



Technical Data Sheet

Date of issue: 08/04/2024

SUBSTRATE PREPARATION

Clean the surface of the tiles with a detergent cleaner and rinse with plenty of water. Particularly for joints, use a suitable sponge to remove detergent residues and mould.

APPLICATION INSTRUCTIONS

Add the special STEPlus additive and stir very well for about 5 minutes.

Dilution: 5-10% with water

Application: Apply TETRALUX in two coats with a roller or brush. It is possible to apply a third coat depending on the shade and gloss of the surface.

Consumption: Approximately 12-14 m²/l on properly prepared surfaces.

General notes:

- For the maximum possible result, it is recommended to use the mixture of the paint with the special additive STEPlus within 10 days.
- The product is applied in room temperature conditions, from 12°C to 25°C.
- Optimum performance and adhesion of the product is achieved after 15-20 days from application. During this period, avoid direct impact, abrasion and surface cleaning.
- To clean painted surfaces, use a mild detergent and a soft sponge.
- Wash tools immediately after application with water and detergent (if necessary).

STORAGE

Keep the packages sealed in their original form and in storage conditions away from frost, sunlight and temperatures below 5°C and above 35°C

HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION INFORMATION AND GUIDELINES

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

Οι παραπάνω τεχνικές πληροφορίες και οδηγίες βασίζονται στην εμπειρία και στις γνώσεις της εταιρείας. Η εταιρεία εγγυάται την ποιότητα του προϊόντος, αλλά δεν φέρει καμία ευθύνη για φθορές που μπορεί να προκληθούν σε περίπτωση που το προϊόν δεν έχει χρησιμοποιηθεί για την κατάλληλη εφαρμογή και σύμφωνα με τις οδηγίες χρήσης του.