

# CEMENTO

## Decorative waterbased paint

**CEMENTO** of Mondo Bello is a decorative paint that creates marble and microcement coating effect. It applies easily and it enables the immediate completion of the technique. It is available in white and bases that cover all shades through TETRALUX tinting system.

### Characteristics-Advantages

- Easy application
- High coverage
- High durability
- Ready to use



### TECHNICAL INFORMATION

<b>Product type</b>	Paint based on acrylic dispersion of special composition and pigments, aggregates and additives.
<b>Density@25°C</b>	1,53-1,58 gr/ml
<b>Viscosity @25°C</b>	6500-8500 cP
<b>Drying time @25°C, 50% relative humidity</b>	<b>Touch dry:</b> 30 minutes <b>Recoat:</b> After 4 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)
<b>Colors</b>	White and bases
<b>VOC (Volatile Organic Compounds)</b>	EU limit value for this product Category A: "I", Type: WB, Decorative effect coatings): 200g/l (2010). This product contains max 199g/l VOC.

#### DILUTION



Without dilution

#### APPLICATION



Brush, roller, airless spray gun

#### DRYING TIME



30 minutes

#### COVERAGE



8 m<sup>2</sup>/l

#### PACKAGING



0,75l,3l,10l

TETRALUX

σύστημα χρωματισμού

## Technical Data Sheet

Date of issue: 10/05/2024

### SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesives and loose materials, such as unstable oil coatings, emulsion paints or synthetic plasters. Then prime the surfaces as appropriate.

### APPLICATION INSTRUCTIONS

**Application method:** Roller, brush or glove and stainless steel spatula.

**Application: 1<sup>st</sup> layer:** On a primed surface, apply a layer of **CEMENTO**, leaving enough product on the surface, with a roller, brush or glove. After that and before the paint dries, level the entire surface with a stainless steel spatula with irregular movements.

After about 5 minutes, repeat the same process with the spatula and level the surface.

**2<sup>nd</sup> layer:** After completely drying and at least after 4 hours, apply another layer of **CEMENTO** in the same way and repeat the same procedure with the spatula. After about 5 minutes, repeat the same process with the spatula and level the surface.

When the paint begins to dry, press the spatula over the whole surface once or twice in order to polish it and appear the effect. The more you press, the more intense the effect will be.

**Extra protection with wax:** For extra protection and glossy effect, apply a layer of Cera Veneziano wax with a sponge and after it dries, polish with a cotton cloth or polisher. The surface you have waxed with CERA Veneziano is shiny and completely waterproof while the other is matt and absorbent.

**Coverage:** About 8 m<sup>2</sup>/l per layer on prepared surfaces.

### Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary). Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

### STORAGE

Keep the packages sealed in their original form and in storage conditions away from frost, sunlight and temperatures below 5°C and above 35°C

### HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION INFORMATION AND GUIDELINES

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.