



TECHNICAL DATA SHEET

ACRYLUX-PU SP553

Product description

Two-component acrylic, aliphatic polyurethane swimming pool paint of high crosslinking degree with very high gloss and very high durability.

Intended uses

Polyurethane finishing coating for interior and exterior swimming pools. It has very good gloss and colour retention as well as excellent resistance to water and to sunlight.

Product data

Indicative film thickness, dry:	50 µm			
Indicative film thickness, wet:	107 µm			
Theoretical coverage:	9,4 m ² /l			
Suggested dry film thickness:	40-60 µm			
Gloss (GU 60 °)	Very Gloss (>90)			
Solids by volume	47 %			
Density (A+B)	1,19 gr/ml			
Mixing ratio A:B	3:1 per volume			
Working pot life	2h (23±2 °C) Time varies with increasing or decreasing temperature and relative humidity.			
Indicative drying times and overcoating/ Relative humidity 50%±5	°C	Touch Dry min	Hard Dry hours	Overcoating hours
	15°	30min	2h	24h
	25°	20min	1,5h	16h
Colours	Blue as well as other colours on request			
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: “j”, Type: SB, Two-pack reactive performance coatings for specific end use such as floors: 500g/l (2010). This product contains max 499g/l VOC.			



Surface preparation and application

Surfaces must be clean, dry and free of oily substances and deposits of other materials which will prevent or affect adhesion. Prior to application, surfaces must be assessed and treated accordingly.

The use of vacuum cleaner and thorough cleaning is recommended.

Application: Apply in two layers. Dilute with more diluent for the first layer.

Application methods

Brush and Roller: Care must be taken to achieve the specified dry film thickness.

Thinner solvent

Brush and Roller: 25-30% (W) for the first layer and 10-15% for the second with Thinner 812

Cleaning solvent

Thinner 812

Application conditions

In conditions of high relative humidity (80-85%), good ventilation conditions are essential. Substrate temperature shall be at least 3°C above the dew point and always above 0°C. Application at ambient air temperatures below 5°C and above 30°C is not recommended.

Safety

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

Remarks

Caution

This product is for professional use only. The applicators and operators shall be trained, experienced and have the capability and equipment to mix/stir and apply the coatings correctly. Applicators and operators shall use appropriate personal protection equipment when using this product.

**Storage**

Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.