



TECHNICAL DATA SHEET

Date of issue: 2025

CERA VENEZIANO

DESCRIPTION

Special protective wax for surfaces decorated with STUCCO VENEZIANO and CEMENTO. It waterproofs the surface, highlights the shade of the decorative paint and gives a gloss finish.



TECHNICAL CHARACTERISTICS

Density	: 0,8 - 0,81 (EAOT EN ISO 2811 20°C)
Viscosity	: Paste
Thinning	: Without dilution
Coverage	: 35m ² /l on surface painted with STUCCO VENEZIANO 30m ² /l on surface painted with CEMENTO
Packaging	: 750ml, 3l
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "i", Type:SB, One-pack performance coatings: 500g/l (2010). This product contains max 499g/l VOC.
Painting tools	: Cotton fabric or long hair glove Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No804.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2025

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

The product does not require dilution.

Apply one thin layer of CERA VENEZIANO with a cotton fabric of a longhair glove and apply it evenly over the entire surface. After 3 hours and after drying, rub gently with a cotton fabric or a lubricant to polish the surface.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.