



## TECHNICAL DATA SHEET

Date of issue: 2021

### ACRYLIC WATERBASED PRIMER

#### DESCRIPTION

It is a whitish water based undercoat for emulsion and acrylic paints. Creates better adhesion conditions and stabilizes the surface. It has very high coverage and is the most economic wall primer.



#### TECHNICAL CHARACTERISTICS

Density	: 1,29 - 1,32 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 5.000 - 7.000 mPas (ASTM D2196-86 25°C)
Thinning	: Dilute with water at a ratio of 1 part primer 4 parts water
Coverage	: 25 - 30m <sup>2</sup> /lt per layer
Drying time	: Touch dry after 1 hour
Packaging	: 0.75lt, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "h", Type:WB, Binding primers: 30g/l (2010). This product contains max 29g/l VOC
Painting tools	: Brush, roller or pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHES TZELOS EV. ANASTASIOS & Co E.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, [www.tetralux.gr](http://www.tetralux.gr), e-mail: [contact@tetralux.gr](mailto:contact@tetralux.gr)



## TECHNICAL DATA SHEET

Date of issue: 2021

---

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.