



TECHNICAL DATA SHEET

Date of issue: 2023

PRIMER SOLLIEVO

DESCRIPTION

Acrylic water based primer containing fine quartz aggregates. Suitable for improving adhesion on smooth low absorbent surfaces as well as absorbent or slightly flaking surfaces.



TECHNICAL CHARACTERISTICS

Density	: 1,44 - 1,48(EAOTENISO 2811 20°C)
Viscosity	: 11000 -17000 mPas(ASTM D2196-86 25°C)
pH	: 8.6-8.9(ASTM E70)
Thinning	: 5-10% with water
Coverage	: 10-12 m ² /l
Drying time	: Touch dry after 1 hour and recoatable after 2-3 hours
Colors	: Unlimited number of shades through tinting system of TETRALUX.
Packaging	: 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "g", Type:WB, primers: 30g/l (2010). This product contains max 29g/l VOC
Painting tools	: Brush, roller Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

MANUFACTURE PAINTS AND VARNISHESTZELOSEV. ANASTASIOS&CoE.E.

5A SQUARE 570 22 SINDOS, INDUSTRIAL AREA OF THESSALONIKI

TEL: 2310 796110, FAX: 2310 723096, www.tetralux.gr, e-mail: contact@tetralux.gr



TECHNICAL DATA SHEET

Date of issue: 2023

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.