

## Technical Data Sheet

Date of revision: 20/01/2025

# AQUA VARNISH MB25

## Matt varnish for decorative coatings Mondo Bello

**Aqua Varnish MB25** is a ready to use water soluble matt acrylic-based varnish. It is ideal for the protection and sealing of Mondo Bello series decorative coatings. It protects decorative coatings from moisture and daily wear, highlights the colours and keeps them bright for a long time. It is easy to apply, does not yellow and dries quickly. It spreads evenly, has great durability without flaking or cracking and creates wonderful matt finish.

### Characteristics-Advantages

- Easy application
- Even spreading
- Quick drying
- Highlights the colours
- Protects decorative coatings Mondo Bello



### TECHNICAL INFORMATION

<b>Product type</b>	Varnish based on water based acrylic dispersion and additives.
<b>Density @25°C</b>	1,00 ±0,03 gr/ml
<b>Viscosity @25°C</b>	45,0-55,0 Krebs Units
<b>Drying time @25°C, 50% relative humidity</b>	<b>Touch dry:</b> 30 minutes <b>Recoat:</b> After 6 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)
<b>Colors</b>	Transparent
<b>VOC (Volatile Organic Compounds)</b>	EU limit value for this product Category A: "i", Type: WB, One-pack performance coatings: 140g/l (2010). This product contains max 139g/l VOC

### DILUTION



without dilution

### APPLICATION



Brush, roller, sponge

### DRYING TIME



30 minutes

### COVERAGE



17-20m<sup>2</sup>/l

### PACKAGING



0,375l,0,75l

## Technical Data Sheet

Date of revision: 20/01/2025

### SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the product.

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

### DIRECTIONS FOR USE

**Application method:** Roller, brush, sponge

**Application:** Apply one or two thin coats of **Aqua Varnish MB25**.

**Drying time @25°C, 50% relative humidity:** Touch dry: 30 minutes **Recoat:** After 6 hours. Times may vary depending on the temperature, humidity, film thickness, color and air movement.

**Coverage:** 17-20 m<sup>2</sup>/l per layer

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.

### Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

### STORAGE

Keep the containers closed in their initial form and in conditions away from frost, sunlight and temperatures below 5°C or above 35°C.