

Technical Data Sheet

Date of issue: 10/09/2025

READY ACRYL

100% acrylic, paint for exterior use

READY ACRYL is a high quality 100% acrylic paint for exterior use. It is an innovative product which does not require dilution and is ready to use. It applies easily, without splashing, spreads perfectly and gives a smooth matt surface. It has high performance and high coverage. It is characterized by high whiteness for whites and bright indelible shades for colored. It is applied on any previous painted or new surface such as plaster, concrete, wood etc., offering a matt surface. Ideal for painting External Thermal Insulation Composite System. It has great resistance to adverse weather conditions and alkali. The colors are unchanged over time.

Characteristics-Advantages

- Ready to use without dilution
- Easy application without paint splatter, spreads perfectly
- High performance and coverage
- High whiteness for whites and bright shades for colored



TECHNICAL INFORMATION

Product Type	Paint based on acrylic dispersion of special composition and pigments, aggregates and additives.
Density @25°C	1,40-1,45 gr/ml
Viscosity @25°C	90,0-100,0 Krebs Units
Drying Times @25°C, 50%	Within 60 minutes
	Recoat: After 2-3 hours
Relative Humidity	These times may vary depending on temperature, humidity, film thickness and air mobility.
Shades	White and unlimited number of light shades through tinting system of TETRALUX (check the colored products before application in order to avoid differences in shade)
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "c", Type: WB, Exterior walls of mineral substrate: 40g/l (2010). This product contains max 39g/l VOC



DILUTION

Ready to use



APPLICATION

Brush, roller, airless spray gun



DRYING TIME

1 hour



COVERAGE

10-12m²/l



PACKAGING

0,75l,3l,10l



Technical Data Sheet

Date of issue: 10/09/2025

SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesives and loose materials, such as unstable oil coatings, acrylic paints or synthetic plasters. Then prime, as recommended below:

Type of substrate	Primer
Stable plaster with normal absorbency	-ACRYLIC water based primer dilution 1:3
Porous absorbent plaster	-TETRADUR water based dilution 2:1 -ACRYLIC water based primer dilution 1:1
Concrete	-TETRADUR water based dilution 2:1
Old similar paint	-Direct application -or preventively ACRYLIC water based primer dilution 1:3
Old absorbent paint	-TETRADUR water based dilution 1:1
Filled cracks, holes, etc	-TETRADUR water based dilution 2:1

may vary depending on the temperature, humidity, film thickness, shade and air movement.

Coverage: 10-12m²/l per coat on smooth surfaces. On uneven surfaces, consumption will be higher.

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

STORAGE

Keep the packages sealed in their original form and in storage conditions away from frost, sunlight and temperatures below 5°C and above 35°C.

HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION INFORMATION AND GUIDELINES

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

APPLICATION INSTRUCTIONS

Application method: Roller, brush, airless spray gun.

Dilution: Stir well and apply directly, without dilution. The paint is ready to use.

Application: Apply two coats of **READY ACRYL**. Depending on the substrate and the shade, an additional coat may be needed.

Drying time @25°C, 50% Relative humidity: Touch dry: 60 minutes **Recoat:** After 2-3 hours. Times

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.