

EMULSION PAINT VELVET

Emulsion paint for indoor use

EMULSION PAINT VELVET is matt ecological emulsion paint for indoor use. It is recommended for painting walls, ceilings made of plaster, concrete, ceramic material, for repainting old coatings and it is suitable for fine skim coat surfaces and dry construction boards. It provides excellent hiding power and coverage. It offers pleasant, clean atmosphere and spaces ready for use. It is certified according to the criteria of Eco labeling Council of EU and it contributes to better indoor air quality with French VOC Class A+ certification. It is suitable for professional use.

Characteristics-Advantages


- Easy application
- High performance and coverage
- Economical and reliable solution
- Velvet matt finish



TECHNICAL INFORMATION

Product Type	Paint based on vinyl dispersion of special composition and pigments, aggregates and additives.
Density @25°C	1,51-1,55 gr/ml (for white and bases)
Viscosity @25°C	110,0-115,0 Krebs Units
Drying Times @25°C, 50% Relative Humidity	<p>Within 60 minutes</p> <p>Recoat: After 2-3 hours</p> <p>These times may vary depending on temperature, humidity, film thickness and air mobility.</p>
Shades	White and unlimited number of light shades through tinting system of TETRALUX (check the colored products before application in order to avoid differences in shade)
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "a", Type: WB, Interior matt walls and ceilings (Gloss<25@60°): 30g/l (2010). This product contains max 9g/l VOC

DILUTION



APPLICATION



DRYING TIME



COVERAGE



PACKAGING



Technical Data Sheet

Date of issue: 15/04/2026

SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesives and loose materials, such as unstable oil coatings, emulsion paints or synthetic plasters. Then prime, as recommended below:

	Primer
Stable plaster with normal absorbency	-ACRYLIC water based primer dilution 1:3
Porous absorbent plaster	-TETRADUR water based dilution 2:1 -ACRYLIC water based primer dilution 1:1
Fine skim coat surface	-TETRADUR water based dilution 2:1
Plaster board	-TETRADUR water based dilution 2:1 or -FILLING plaster board primer for filling and even surface
Concrete	-TETRADUR water based dilution 2:1
Old similar paint	-Direct application -or preventively ACRYLIC water based primer dilution 1:3
Old absorbent paint	-TETRADUR water based dilution 1:1
Hydrochroma	-TETRADUR water based dilution 1:1 first coat -TETRADUR water based dilution 2:1 second coat
Filled cracks, holes, etc	-TETRADUR water based dilution 2:1

APPLICATION INSTRUCTIONS

Application method: Roller, brush, airless spray gun. Airless spray: Spray angle: 50°, Nozzle size: 0.018" to 0.021", Gun pressure: 150 to 180bar.

Dilution: Dilute with water and stir well

- White Base P 10% v/v
- Base D 5-10% v/v

Application: Apply two coats of **EMULSION PAINT VELVET**. Depending on the substrate and the shade, an additional coat may be needed.

Coverage: 10-12m²/l per coat on smooth surfaces. On uneven surfaces, consumption will be higher.

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

STORAGE

Keep the packages sealed in their original form and in storage conditions away from frost, sunlight and temperatures below 5°C and above 35°C.

HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION INFORMATION AND GUIDELINES

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.