

Technical Data Sheet

Date of issue: 15/07/2026

METALLIC AQUA

Decorative acrylic water based paint

METALLIC AQUA is an acrylic, water based, multipurpose paint, for painting, crafting and decoration. It has great hiding power, it is easy to use and it can be applied on the most of the surfaces. It is odorless and has great resistance to adverse weather conditions, wear and washing. Suitable for the decoration of surfaces of concrete, stone, clay, plaster, wood, paper, iron, canvas, polystyrene etc, for interior and exterior use.

Characteristics-Advantages

- Great hiding power
- Easy application
- Impressive metallic finish



TECHNICAL INFORMATION

Product type	Paint based on acrylic dispersion of special composition and metallic pigments.
Density@25°C	1,18-1,23 gr/ml
Viscosity @25°C	9500-10500 mPas
Drying time @25°C, 50% relative humidity	Touch dry: 60 minutes Recoat: After 3-5 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)
Colors	Gold, silver, bronze, copper (check the colored products before application in order to avoid differences in shade)
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "I", Type: WB, Decorative effect coatings: 200g/l (2010). This product contains max 100g/l VOC

DILUTION



0-5% v/v
with water

APPLICATION



Brush, roller, airless spray gun

DRYING TIME



1 hour

COVERAGE



12-16m²/l

PACKAGING



250ml,
750ml

Technical Data Sheet

Date of issue: 15/07/2026

SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesives and friable materials, such as unstable coatings of oil paints or synthetic plasters. Then apply the product directly. For application on iron, it is recommended to apply an anti-rust primer first. Synthetic smooth surfaces are treated with suitable sandpaper to enhance adhesion.

DIRECTIONS FOR USE

Application method: Roller, brush, airless spray gun.

Dilution: 0-5% v/v with water

Application: Apply one or two coats of **METALLIC AQUA**.

Coverage: 12-16 m²/l per layer on well prepared surfaces..

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 10°C or above 33°C.

STORAGE

Keep the containers closed in their initial form and in conditions away from frost, sunlight and temperatures below 5°C or above 35°C.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.