

CHALK PAINT

Decorative chalk paint

Chalk paint of Mondo Bello is a decorative water-based paint that creates a mat finish and plenty of decorative effects, two-colour distressed paint effect, vintage style, shabby chic. Ideal for restoration and decoration of wooden furniture, walls or objects made of various materials such as wood, glass, iron, marble, plastics, wallpaper, brick, cement, etc. It is applied to all painted or varnished surfaces. It dries quickly and it has great hiding power.

Characteristics-Advantages

- Easy application
- Great hiding power
- Quick drying
- Easy sanding



TECHNICAL INFORMATION

Product type	Paint based on water based acrylic dispersion and pigments, aggregates and additives.
Density @25°C	1,49-1,55 g/ml (white and bases)
Viscosity @25°C	108,0-120,0 Krebs Units (white and bases)
Drying time @25°C, 50% relative humidity	Touch dry: 30 minutes Recoat: After 6 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)
Colors	White, ready shades and unlimited number of shades through tinting system of TETRALUX (check the colored products before application in order to avoid differences in shade)
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "I", Type: WB, Decorative effect coatings: 200g/l (2010). This product contains max 199g/l VOC

DILUTION



0-10% with water

APPLICATION



Brush, roller

DRYING TIME



30 minutes

COVERAGE



12m²/l

PACKAGING



0,375l, 0,75l

TETRALUX

σύστημα χρωματισμού

Technical Data Sheet

Date of revision: 26/7/2023

SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesive residue and loose materials, such as unstable oil coatings, emulsion paints or synthetic plasters. Then prime, as recommended below:

Type of substrate	Primer
Plaster, putty surface, plaster board, concrete (New surfaces or surfaces in bad condition)	-TETRADUR water based dilution 2:1 with water
Old and new wooden surfaces	For better adhesion use sandpaper 120 grit and up
Glass, marble, wallpaper	Application of Chalk paint
New metal surfaces	Preparation with Tetra rust primer
Old painted metal surfaces	For better adhesion, use sandpaper 120 grit and up.

DIRECTIONS FOR USE

Application method: Roller, brush.

Dilution: Dilute 5-10% v.v. with water and stir well

Application: Apply one or two coats of **Chalk paint** depending on the desirable result.

For dichromate: Apply two coats of different shades. After the surface is dried, sand locally so the first shade appears and the surface gets an impressive vintage or shabby chic look.

Apply Chalk wax or Chalk varnish for different vintage result and extra protection.

Drying time @25°C, 50% relative humidity: Touch dry: 30 minutes **Recoat:** After 6 hours. Times may

vary depending on the temperature, humidity, film thickness, color and air movement.

Coverage: 12 m²/l per coat on smooth surfaces.

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

STORAGE

Keep the containers closed in their initial form and in conditions away from frost, sunlight and temperatures below 5°C or above 35°C.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.