

# CHALK WAX

## Wax for chalk paint

**Chalk wax of Mondo Bello** is a special finishing wax paste, applied on surfaces painted with Chalk paint of Mondo Bello for extra protection. It offers a velvet and smooth surface. It protects from scratches and moisture, while enhancing the tone of chalk paint or natural wood. It is lightly perfumed.

### Characteristics-Advantages

- Easy application
- Protection of surfaces painted with chalk paint
- Velvet, smooth finish



### TECHNICAL INFORMATION

|                                                 |                                                                                                                                                                    |
|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product type</b>                             | Wax paste based on paraffin dispersion                                                                                                                             |
| <b>Density @25°C</b>                            | 0,9±0,15gr/ml (clear and shades)                                                                                                                                   |
| <b>Drying time @25°C, 50% relative humidity</b> | <b>Touch dry:</b> 30 minutes<br><b>Recoat:</b> After 30 minutes<br>(Times may vary depending on the temperature, humidity, film thickness, shade and air movement) |
| <b>Colors</b>                                   | Transparent, antique, white, black, amber (check the colored products before application in order to avoid differences in shade)                                   |
| <b>VOC (Volatile Organic Compounds)</b>         | EU limit value for this product Category A: "i", Type: SB, One-pack performance coatings: 500g/l (2010). This product contains max 499g/l VOC                      |

#### DILUTION



without dilution

#### APPLICATION



Brush or cotton fabric

#### DRYING TIME



30 minutes

#### COVERAGE



15 m<sup>2</sup>/l

#### PACKAGING



250ml

## Technical Data Sheet

Date of revision: 26/7/2023

### DIRECTIONS FOR USE

**Application method:** Brush or good quality cotton fabric.

**Dilution:** Without dilution.

**Application:** Apply **Chalk wax** on surfaces painted with chalk paint. Apply one thin coat and after it's dried, apply a second one. Between coats, wait 30 minutes for the wax to be absorbed by the surface.

**Drying time @25°C, 50% relative humidity: Touch dry:** 30 minutes **Recoat:** After 30minutes. Times may vary depending on the temperature, humidity, film thickness, color and air movement.

**Coverage:** 15 m<sup>2</sup>/l per coat.

#### Remarks:

- Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No804 or No806 and then wash with water and soap (if it is necessary). Do not dispose liquids of cleaning into environment.
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

### STORAGE

Keep the containers closed in their initial form and in conditions away from frost, sunlight and temperatures below 5°C or above 35°C.

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.