Technical Data Sheet
Date of issue: 10/05/2024

STUCCO VENEZIANO

Decorative finish for interior use

STUCCO VENEZIANO of Mondo Bello is decorative lime based stucco. The final result has appearance of marble. Although the usual means are used, the appearance differs in each application with gradation of tones and shapes, depend on the applicator. It is easy to apply, it enables the technique to be completed immediately. Available on a base that can be colored to order.

Characteristics-Advantages

- Easy application
- Excellent marble effect
- Ready to use

TECHNICAL INFORMATION

Product type	Lime based stucco based on special pigments, aggregates and additives.
Density@25ºC	1,70-1,80 gr/ml
Viscosity @25ºC	Paste 90000-120000 cP
Drying time @25ºC, 50% relative humidity	**Touch dry:** 30 minutes **Recoat:** After 4-6 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)
Colors	Base that can be tinted
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "l", Type: WB, Decorative effect coatings): 200g/l (2010).This product contains max 199g/l VOC.



SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesives and loose materials, such as unstable oil coatings, emulsion paints or synthetic plasters.

APPLICATION INSTRUCTIONS

Application method: Stainless steel trowel.

Application: On a smooth surface, prime using **PRIMER STUCCO**. Tint in the desirable shade. If it's necessary, add thickener while stirring, to increase the viscosity to the desired workability.
1st layer: Apply one layer of **STUCCO VENAZIANO** of Mondo Bello.
2nd layer: After 6 hours stir **STUCCO VENEZIANO** to soften and apply a second layer, working the trowel randomly. When about a square meter of surface is finished and after about 30 seconds, press with a stainless steel trowel in order to create a shiny effect. Continue in the same way for the rest surface. The more you press, the more intense will be the effect.
Extra protection with wax: For extra protection and glossy effect, apply a layer of CERA VENEZIANO wax with a sponge and after it dries, polish with a cotton cloth or polisher. The surface you have waxed with CERA VENEZIANO is shiny and completely waterproof.

Drying time @25ºC, 50% relative humidity: Touch dry: 30 minutes **Recoat:** After 4-6 hours (Times may vary depending on the temperature, humidity, film thickness, shade and air movement)

Coverage: About 4 - 5 m²/kg per coat on prepared surfaces.

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

STORAGE

Keep the packages sealed in their original form and in storage conditions away from frost, sunlight and temperatures below 5°C and above 35°C

HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION INFORMATION AND GUIDELINES

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.