

AQUA PRIMER

Ecological water based primer (EU Ecolabel: EL/044/021)

AQUA PRIMER is a high quality ecological water-based primer, suitable for indoor and outdoor use as an undercoat for water-based enamels on wooden surfaces. It is a product certified according to the criteria of the EU eco-label awarding council, user and environmentally friendly. It is easy to apply and shows excellent adhesion on new and painted surfaces. It spreads evenly, fills the wood surface, is easy to sand and is an ideal substrate for water-based enamels.

Characteristics-Advantages

- Easy application
- Excellent adhesion
- Excellent leveling and filling properties
- Easy sanding



TECHNICAL INFORMATION

Product Type	Water based primer based on aqueous polymer dispersion of special composition and pigments, aggregates and additives.
Density @25°C	1,25±0,02 g/ml
Viscosity @25°C	95,0-100,0 Krebs Units
Drying Times @25°C, 50% Relative Humidity	Within 60 minutes Recoat: After 5-6 hours These times may vary depending on temperature, humidity, film thickness and air mobility.
Shades	White
VOC (Volatile Organic Compounds)	EU limit value for this product Category A: "d", Type: WB, Interior/exterior trim and cladding paints for wood and metal is: 130g/l (2010). This product contains max 79g/l VOC

DILUTION



5% for brush or roller
10-20% for spray gun

APPLICATION



Brush, roller, airless spray gun

DRYING TIME



1 hour

COVERAGE



10 m²/l

PACKAGING



0,75l, 2,5l, 10l

TETRALUX

σύστημα χρωματισμού

Technical Data Sheet

Date of issue: 05/07/2023

SUBSTRATE PREPARATION

The substrate must be stable, dry, clean and free of substances that may affect the shade and the adhesion of the paint. Clean the surface from dust, oils, adhesives and loose materials, such as unstable oil coatings, emulsion paints or synthetic plasters.

APPLICATION INSTRUCTIONS

Dilution: Dilute with water and stir well

- 5% w/w for roller or brush
- 10-20% w/w for airless spray gun

Application: Apply one or two coats of **AQUA PRIMER**. For a perfect finish, sand the surface with appropriate sandpaper before applying the topcoat.

Coverage: 10m²/l per coat on properly prepared surfaces.

Remarks:

- Wash your equipment immediately after the application, with water and soap (if it is necessary).
- Avoid the product application if the ambient and surface temperature is below 5°C or above 35°C.

STORAGE

Keep the packages sealed in their original form and in storage conditions away from frost, sunlight and temperatures below 5°C and above 35°C.

HEALTH, SAFETY AND ENVIRONMENTAL PROTECTION INFORMATION AND INSTRUCTIONS

Handle with care. Before and during use, follow all safety instructions on the packaging and containers, consult TETRALUX Safety Data Sheets and follow all local or national safety regulations.

The above technical information is based on the experience and the knowledge of the company. The company guarantees the quality of the product, but bears no responsibility for any damages caused if the product has not been used properly and in accordance with its instructions for use.